

SPH
SPIDER PLATFORM HIRE

Series Spider 22.10

Product Data Sheet

Self-propelled tracked vehicles.

Product Description

The Spider 22.10 is a versatile, high-performance tracked spider lift, designed for precision access in both indoor and outdoor environments, combining exceptional reach, stability, and maneuverability.

Key Features :

- 230 kg in the basket
- Electric battery or HYBRID version on request
- Easy access to every component subject to maintenance.
- Simple but precise to use.
- Equipped with radio remote control
- Triple stabilization set up and automatic outreach
- Multi-width stabilizer settings to enable machine to set up in confined spaces
- Air & Water & 220 Vac outlets into the basket

For more information:

spiderplatform.co.uk

hello@spiderplatform.co.uk | 01226 885078

Technical Specifications :

Maximum working height:	m	21,70		
Floor height:	m	19,70		
Maximum side outreach:	m	10,30		
Rotation angle of tower:	°	365		
Basket dimensions:	m	1,50 x 0,70		
Basket rotation angles:	°	90+90		
Maximum basket capacity:	Kg	230		
Length closed (no basket):	m	5,97 (5,28)		
Minimum width closed:	m	0,98		
Minimum height closed:	m	2,06		
Overall dimensions stabilised:	m	Wide 3,87 x 3,94	Narrow 2,57 x 5,05	
Maximum horizontal inclination:	%	16° (29%)		
Maximum side inclination:	%	17° (31%)		
Maximum Speed	Km/h	1,5	0,8	1,5
Weight in work conditions:	Kg	2980*	3260*	3260*
Ground pressure stowed machine:	KN/m ²	2,94	3,21	3,21
Ground pressure on stabilisers:	KN/m ²	1,91	2,09	2,09
Max point load on one stabiliser:	KN	21	23	23
Z602 Kubota diesel engine:	HP/rpm	14/3600	-	14/3600
Electric motor 220 Vac	CV/KW	3 / 2,2	3 / 2,2	-
Electric motor 24 Vdc	CV/KW	-	7,4/5,5	7,4/5,5
24Vdc Lead Acid (Battery Capacity)	Ah	-	2x210	1x210
24Vdc Lithium Ion (Battery Capacity)	Ah	-	400	300
Lead Acid (Battery Charger)	Ah	-	45	45
Lithium Ion (Battery Charger)	Ah	-	100/50	100/50

*Subject to change, depending on configuration.

Contact

spiderplatform.co.uk  Yorkshire, UK 

hello@spiderplatform.co.uk 